

Rehandling Buckets

Overview

With over 30 years of design behind it, the Cherry range of Rehandling Buckets have proven their popularity and worth over years of production. Designed to maximise the working angles, the Bucket is built specifically to suit your handler. A host of extras can be added to suit your application, ranging from Bolt On Leading Edges, to Spill Guards.

Features

Support Straps, 150 x 12mm run continuously around/across the bucket

Side Stiffeners, 80 x 12mm down either side

Leading Edge, protects against undue wear and tear and acts as a main strengthening component

Bucket Angle, purpose built to suit your machine for maximum crowd and dump.

Specification

Part No.	Width	Height	Depth	m3	CuFt	Kilos
CB09FW	2450mm (8')	750	770	0.89	32	416
CB10FW	2450mm (8')	840	1120	1.50	53	437
CB11FW	2450mm (8')	900	1140	1.80	64	544
CB50FW	2450mm (8')	960	1260	2.11	74	580
CB09F	2286mm (7'6")	750	770	0.84	30	390
CB10F	2286mm (7'6")	840	1120	1.41	50	410
CB11F	2286mm (7'6")	900	1140	1.69	60	510
CB50F	2286mm (7'6")	960	1260	1.98	70	550
CB09AF	2133mm (7')	750	770	0.79	28	365
CB10AF	2133mm (7')	840	1120	1.30	46	400
CB11AF	2133mm (7')	900	1140	1.58	56	490
CB09SF	1980mm (6'6")	750	770	0.73	26	320
CB10SF	1980mm (6'6")	840	1120	1.21	43	380
CB11SF	1980mm (6'6")	900	1140	1.47	52	415



Tel – 01608 678 197

Fax – 01608 677 778

Email – sales@cherryproducts.co.uk

Website – www.cherryproducts.co.uk

